

BEMO ROOF w/HOOK CLIP: ALLOWABLE UPLIFT LOADS-PSF

Panel Material	Panel Width	Panel Gauge	Span in feet						
			2.0	2.5	3.0	3.5	4.0	4.5	5.0
Alum.	305 mm	.032	81.2	75.0	68.8	62.6	56.3	50.1	43.9
		.040	114.1	109.4	104.6	99.9	95.2	90.4	85.7
	400 mm	.032	50.6	49.6	48.6	47.6	46.5	45.5	44.5
		.040	78.4	76.0	73.7	71.3	68.9	66.6	64.2
	500 mm	.032	28.2	27.5	26.8	26.2	25.5	24.8	24.1
		.040	57.0	54.9	52.7	50.6	48.4	46.3	44.1
Steel	305 mm	24 ga.	62.7	60.9	59.1	57.4	55.6	53.8	52.0
		22 ga.	117.2	111.6	106.1	100.5	94.9	89.4	83.8
	400 mm	24 ga.	45.7	43.4	41.1	38.8	36.4	34.1	31.8
		22 ga.	75.8	72.7	69.5	66.4	63.2	60.1	56.9
	500 mm	24 ga.	34.2	32.9	31.5	30.2	28.8	27.5	26.1
		22 ga.	47.6	45.6	43.6	41.7	39.7	37.7	35.7

BEMO ROOF w/HALTER: ALLOWABLE UPLIFT LOADS-PSF

Panel Material	Panel Width	Panel Gauge	Span in feet						
			2.0	2.5	3.0	3.5	4.0	4.5	5.0
Alum.	305 mm	.032	59.4	56.1	52.9	49.6	46.3	43.1	39.8
		.040	102.4	96.9	91.5	86.0	80.5	75.1	69.6
	400 mm	.032	47.7	43.9	40.1	36.4	32.6	28.8	25
		.040	74.9	69.9	64.8	59.8	54.7	49.7	44.6
	500 mm	.040	56.3	52.4	48.5	44.7	40.8	36.9	33